

INGESYS

IC2

Rolling Stock Subsystem Controller



INGESYS™ IC2 is a control system aimed at meeting subsystem automation requirements in the railway sector (tram, trains, etc.).

Its compact and robust design according to standards EN50155 and EN45545-2 is adapted to the demanding mechanical, environmental and fire protection requirements of the railway sector.

Compact controller according to rolling stock standards

INGESYS™ IC2 is a controller with a modular structure and a wide range of digital and analogue input/output modules that make possible to offer a technical solution suited to each application at an optimum cost.

A wide variety of standard communication interfaces used in the railway sector are available, which enables the integration of the controller into the train communications networks commonly used in the railway market.

IEC61131-3 standard compatible user programming tools are provided for application development and testing. A comprehensive functions library (mathematical, regulation, data filling, communications, etc.) and the possibility to incorporate user defined functions to these libraries help the user to optimize the application development.

The integration of a web server allows the user to diagnose and monitor remotely the system easily and flexibly to suit their needs.

Oriented to train subsystems control (HVAC, toilets, FDS, doors, galleys, etc.) and to tram control system.

Benefits

- ✓ Compact and robust design
- ✓ Custom-made solution with optimum costs
- ✓ Compliance to railway standards
- ✓ Cost-effective solution

www.ingeteam.com
ingesys.info@ingeteam.com

Ingeteam

	Power Source	
Main Power Supply*	224Vdc (+25% / -30%) Class S2 (EN 50155:2017) 36-48Vdc (+25% / -30%) Class S2 (EN 50155:2017) 72-110Vdc (+25% / -30%) Class S2 (EN 50155:2017)	
Maximum Consumption Dissipated Power	24V @ 300mA / 110V @ 80mA 8W (max.)	
	Processor Module	
Main Processor	32bit, 400MHz	32bit, Dual Core 800MHz
Memory	Up to 128MB	512MB
	Program: 1MB	Program: 4MB
	Data: up to 1MB	Data: up to 4MB
	Non volatil data: 62KB	Non volatil data: 128KB
	Data logging: 32MB (up to 8GB optional)	
Program	IEC61131-3 (specific functions, communication and regulation library), C/C++, Matlab/Simulink	
Monitoring and Maintenance	Embedded Web Server	
	Local LCD Text Display (optional)	
	USB Port for upload / download: firmware, application, data register...	
LAN	2 Ethernet 10/100Base TX M12 (internal switch)	
	Additional 1 Ethernet 10/100Base TX M12 (optional)	
	Protocols: Modbus TCP/IP, TRDP, Ethernet/IP, CIP, PROFINET I/O, SFTP	
Field buses (up to 4 *)	Up to 4 selectable Ports per CPU: CANOpen, Profibus DP, RS232/RS485, MVB ESD+, MVB EMD	
	Input/Output Modules**	
Digital inputs	16 DI (24Vdc @ 3mA) (PNP or NPN)	
	8 DI (24-110Vdc) (PNP or NPN)	
Digital Outputs	16 DO (HSD 24Vdc @ 500mA) (PNP o NPN)	
	8 DO (24VDC @ 2A)	
	8 DO (24-110Vdc @ 0.5A)	
Relay Outputs	3 electromechanical Relay Outputs with switched contacts (150V @ 5A)	
Mixed Digital I/Os	8 DI (24Vdc @ 5mA) + 8 DO (HSD 24Vdc @ 500mA)	
	12 DI (24Vdc @ 5mA) + 4 DO (HSD 24Vdc @ 500mA)	
	4 DI (24Vdc @ 5mA) + 12 DO (HSD 24Vdc @ 500mA)	
Analog Inputs	8 AI ($\pm 10V$ or $\pm 20mA$)	
	8 fast synchronous AI, up to 100Ks/s, for ($\pm 10V$ or $\pm 20mA$) or IEPE accelerometers 10 Temperature inputs (PT100, NTC or Thermocouple)	
Analog Outputs	8 AO ($\pm 10V$ or $\pm 20mA$)	
Motor Control	4 DI (24Vdc@ 5mA) + 1 Encoder input + 1 PWM output (up to 12A) H-bridge topology	
Audio	2 Audio outputs 2W	
	Standards	
Immunity and Emission	EN 50121-3-2:2007	
Temperature Range	EN 50155:2017 [Class TX (-40°C at +70°C)]	
Vibrations	EN 50155:2017 [Body Mounted, Class B] / IEC 61373:2007	
Fire protection	EN 45545-2	
	Mechanical Features	
Assembly	Panel Mount	
Material	Aluminium	
Dimensions (W x H x D)	(149mm to 524mm)*** x 135mm x 34.6mm	

* Optional ** A combination of up to 10 modules *** Depending on the number of I/O modules selected, each with a width of 37.5 mm.