

General Description

INDAR Scope of Supply

Main Generators	<ul style="list-style-type: none"> ○ Output power: 5,625 kVA ○ Voltage: 6,600 V ○ Speed: 720 rpm
Main Propulsion Motors	<ul style="list-style-type: none"> ○ Output power: 3,350 kW ○ Voltage: 3,150 V ○ Speed: 1,100 rpm
Bow Thruster Motors	<ul style="list-style-type: none"> ○ Output power: 2,000 kW ○ Voltage: 3,150 V ○ Speed: 750 rpm
Retractable Thruster Motors	<ul style="list-style-type: none"> ○ Output power: 2,000 kW ○ Voltage: 3,150 V ○ Speed: 750 rpm



Vessel Main Characteristics

○ Owner:	Jan de Nul
○ Length overall:	191.5 m
○ Length between perp.:	175 m
○ Breadth moulded:	40 m
○ Depth moulded:	13.2 m
○ Designing draught:	7.5 m
○ Rock carrying capacity:	31,500 ton
○ Discharge capacity:	2,000 ton/hour
○ Max. discharge depth:	2,000 m

Indar
Ingeteam Group

Your driving force

Indar Electric, S.L.
Polígono Industrial Txara, s/n
20200 BEASAIN - SPAIN
Tel.: 34 943 02 82 00
Fax.: 34 943 02 82 04
marine@indar.ingeteam.com

Indar Electric, S.L.

www.indar.net