

# INGESYS

# IC2

## Rolling Stock Subsystem Controller



INGESYS™ IC2 is a control system aimed at meeting subsystem automation requirements in the railway sector (tram, trains, etc.).

Its compact and robust design according to standards EN50155 and EN45545-2 is adapted to the demanding mechanical, environmental and fire protection requirements of the railway sector.

### Compact controller according to rolling stock standards

INGESYS™ IC2 is a controller with a modular structure and a wide range of digital and analogue input/output modules that make possible to offer a technical solution suited to each application at an optimum cost.

A wide variety of standard communication interfaces used in the railway sector are available, which enables the integration of the controller into the train communications networks commonly used in the railway market.

IEC61131-3 standard compatible user programming tools are provided for application development and testing. A comprehensive functions library (mathematical, regulation, data filling, communications, etc.) and the possibility to incorporate user defined functions to these libraries help the user to optimize the application development.

The integration of a web server allows the user to diagnose and monitor remotely the system easily and flexibly to suit their needs.

Oriented to train subsystems control (HVAC, toilets, FDS, doors, galleys, etc.) and to tram control system.

### Benefits

- ✓ Compact and robust design
- ✓ Custom-made solution with optimum costs
- ✓ Compliance to railway standards
- ✓ Cost-effective solution

Main Power Supply*	Power Source	
	224Vdc (+25% / -30%) Class S2 (EN 50155:2017)	
	36-48Vdc (+25% / -30%) Class S2 (EN 50155:2017)	
Maximum Consumption Dissipated Power	72-110Vdc (+25% / -30%) Class S2 (EN 50155:2017)	
	24V @ 300mA / 110V @ 80mA	
Main Processor	8W (max.)	
	Processor Module	
	IC2-HC	IC2-P
Memory	32bit, 400MHz	32bit, Dual Core 800MHz
	Up to 128MB	512MB
	Program: 1MB	Program: 4MB
Program	Data: up to 1MB	Data: up to 4MB
	Non volatil data: 62KB	Non volatil data: 128KB
Monitoring and Maintenance	Data logging: 32MB (up to 8GB optional)	
	IEC61131-3 (specific functions, communication and regulation library), C/C++, Matlab/Simulink	
	Embedded Web Server	
LAN	Local LCD Text Display (optional)	
	USB Port for upload / download: firmware, application, data register...	
	2 Ethernet 10/100Base TX M12 (internal switch)	
Field buses ( up to 4 *)	Additional 1 Ethernet 10/100Base TX M12 (optional)	
	Protocols: Modbus TCP/IP, TRDP, Ethernet/IP, CIP, PROFINET I/O, SFTP	
	Up to 4 selectable Ports per CPU: CANOpen, Profibus DP, RS232/RS485, MVB ESD+, MVB EMD	
Digital inputs	Input/Output Modules**	
	16 DI (24Vdc @ 3mA) (PNP or NPN)	
	8 DI (24-110Vdc) (PNP or NPN)	
Digital Outputs	16 DO (HSD 24Vdc @ 500mA) (PNP o NPN)	
	8 DO (24VDC @ 2A)	
	8 DO (24-110Vdc @ 0.5A)	
Relay Outputs	3 electromechanical Relay Outputs with switched contacts (150V @ 5A)	
	8 DI (24Vdc @ 5mA) + 8 DO (HSD 24Vdc @ 500mA)	
	12 DI (24Vdc @ 5mA) + 4 DO (HSD 24Vdc @ 500mA)	
Mixed Digital I/Os	4 DI (24Vdc @ 5mA) + 12 DO (HSD 24Vdc @ 500mA)	
	8 AI (±10V or ± 20mA)	
	8 fast synchronous AI, up to 100Ks/s, for (±10V or ± 20mA) or IEPE accelerometers	
Analog Inputs	10 Temperature inputs (PT100, NTC or Thermocouple)	
	8 AO (±10V or ± 20mA)	
	4 DI (24Vdc @ 5mA) + 1 Encoder input + 1 PWM output (up to 12A) H-bridge topology	
Analog Outputs	2 Audio outputs 2W	
	Standards	
	EN 50121-3-2:2007	
Motor Control	EN 50155:2017 [Class TX (-40°C at +70°C)]	
	EN 50155:2017 [Body Mounted, Class B] / IEC 61373:2007	
	EN 45545-2	
Audio	Mechanical Features	
	Panel Mount	
	Aluminium	
Immunity and Emission	(149mm to 524mm)*** x 135mm x 34.6mm	
	Temperature Range	
	Vibrations	
Fire protection	Assembly	
	Material	
	Dimensions (W x H x D)	

\* Optional \*\* A combination of up to 10 modules \*\*\* Depending on the number of I/O modules selected, each with a width of 37.5 mm.