

INGEREV

NEO

THE IDEAL CHARGING STATION

for homes and private properties



The **INGEREV® NEO** is a compact Mode 3 EV charging station that is lightweight and easy to install, making it ideal for charging electric vehicles at home and on private properties. It is available in versions with a Type 2 socket and with a built-in cable, for greater convenience when charging. It also allows for power balancing based on the consumption in the rest of the installation.

It features Bluetooth and its own mobile application to allow users to configure different charging functions. At the same time, it is also possible to monitor the charging, set times and analyse consumption data.

The advanced NEO Pro version also includes Wi-Fi and Ethernet and, optionally 4G.

FUNCTIONALITIES

- Wallbox suitable for outdoor installation.
- 7.4 kW and 22 kW versions.
- Mode 3 vehicle charging.
- Type 2 socket or built-in cable Type 1 or Type 2 for versions with a length of 5 or 7 m.
- Cable hanger included.
- Consumption metering.
- RGB LED status indicators.
- Optional DC leakage sensor.
- Bluetooth 4.2.
- Wifi & Ethernet, only versions NEO Pro.
- Mobile application, Bluetooth connection.
- Access control selection via app.
- Charge programming via app.



Ingeteam

INGEREV

NEO

THE IDEAL CHARGING STATION

for homes and private properties

Inputs & outputs	INGEREV® NEO		INGEREV® NEO Pro	
	Single-phase (NN1)		Single-phase (NP1)	Three-phase (NP3)
Voltage	1ph. + N + PE 230 Vac 15%		1ph. + N + PE 230 Vac 15%	3ph. + N + PE 400 Vac 15%
Rated power	7.4 kW		7.4 kW	22 kW
Frequency	50 / 60 Hz			
Rated current	32 A			
Output connectors	Type 2 Socket (without shutters). Cable Type 1 or 2 ⁽¹⁾		Type 2 Socket (without shutters). Cable Type 2 ⁽¹⁾	
Charging modes	Mode 3			
Standards and safety				
General standards	IEC-61851			
Indirect contacts	DC current leakage detector (optional)			
Functionalities and accessories				
Communications	Bluetooth 4.2		Bluetooth 4.2, Wi-Fi, Ethernet, LTE (optional)	
HMI	Status LED indicator. Mobile application			
General information				
Consumption in stand-by mode	<10 W			
Energy metering	Yes			
Static power management	Separately for each charger		Separately for each charger and for a group of interconnected chargers	
Dynamic power management	Single-phase meter installation (included)	Single-phase meter installation (included)	Three-phase meter installation (optional)	
Cable hanger	Included			
Floor stand	Single and double (optional)			
Cover colour	White or red			
Operating temperature	-25 to 40 °C			
Humidity	95%			
Maximum height	2000 m			
Weight (including 5 m and 7 m cable)	3.75 kg / 4.35 kg		4.35 kg / 4.95 kg	
Dimensions	365 x 220 x 105 mm			
Housing	ASA PC flame retardant (V0)			
Protection rating	IP54 / IK10			
Marking	CE			
Directives	Low Voltage Directive: 2014/35/EU EMC directive: 2014/30/EU			

Notes: ⁽¹⁾ Different lengths available: 5 m and 7 m.

Ingeteam