



10TL M / 15TL M / 20TL M / 30TL M

THREE-PHASE HYBRID INVERTER WITH TWO OR THREE PV MPPTs

THE BEST SOLUTION FOR RESIDENTIAL OR COMMERCIAL SOLAR+STORAGE SYSTEMS

The INGECON® SUN STORAGE 3Play TL M hybrid inverter makes it possible to combine photovoltaic generation and energy storage with no need for any additional PV inverters.

Two or three MPPT system

This inverter features with two or three maximum power point tracking (MPPT) system, that allows it to draw the maximum power from the PV array, including roof-mounted installations with different orientations or with partial shading.

Three phase unbalance function

This inverter has support for unbalanced three-phase consumption on both grid side and backup side.

EMS Inside

The inverter is equipped as standard with an energy management system (EMS). The EMS permits more advanced functionalities, such as self-consumption or peak-shaving. Thanks to the built-in EMS, the installation can be monitored at all times via a PC or mobile phone with the free INGECON® SUN Monitor application, available at Play Store and App Store.

Start-up and monitoring

Fast and easy start-up and display of data and graphics through the integrated user interface. Furthermore, users can easily upgrade the inverter firmware from the application, through a PC, tablet or mobile.

5 year warranty, extendible up to 10 years.

10TL M / 15TL M / 20TL M / 30TL M

The best solution for residential or commercial solar+storage systems

OPERATING MODES:

- Self-consumption mode

This operating mode is directed at grid connection systems with renewable energy sources, in order to minimise grid unbalance three-phase consumption. If the energy generated is greater than demand, then any surplus energy could either be used to charge the batteries or to be injected into the grid. In addition, it features a back-up and a peak shaving functionality. Also, the user can programme the charge / discharge times of the batteries.

- Stand-alone mode

The INGECON® SUN STORAGE 3Play TL M inverter generates a stand-alone AC grid and acts as a grid manager, guaranteeing the correct balance between PV generation, unbalance three-phase consumption and the storage system. It is equipped with a relay for the neutral-to-earth connection of the system loads in order to create a TT stand-alone network. Moreover, the inverter permits the connection of an auxiliary generator, which can be started-up through a potential-free output for charging the batteries.


Protections

- AC overvoltages.
- Insulation faults.
- Short-circuits and overloads at the output.
- DC breaker for the PV array.
- Anti-islanding with automatic disconnection.
- Surge Arrester: Type II for 10TL M, Type III for 15-30TL M.
- AFCI with automatic disconnection.
- PV input reverse polarity protection.
- Battery input reverse polarity protection.


Features

- Two or three MPPT system up to 150-200% PV input.
- RS-485 and Ethernet communication for the wattmeter.
- Wi-Fi and Ethernet communication.
- CAN Bus 2.0 communication for the BMS (Battery Management System).
- 2 configurable digital inputs.
- 2 configurable potential free outputs.
- Pre-charging system at the battery input.
- Relay for the neutral to earth connection for critical loads in type TT / TN-S / TN-C-S installations.
- Rapid start-up and view of the installation thanks to the INGECON® SUN Monitor user interface.
- Possibility of operating just from the PV array and of adding the storage system at a later date.
- Suitable for indoor and outdoor installations (IP65).
- Back-up functionality available for self-consumption installations.
- Peak shaving functionality.
- Configuration of the battery charge / discharge times.
- Modbus TCP / Wi-Fi communication with EV chargers.
- DRMO included (for the Australian market).
- Three phase unbalance function.


Stand-alone diagram



Self-consumption diagram



Size and weight (mm)



10TL M: 560
15-30TL M: 596

10TL M: 218.3
15-30TL M: 235

10TL M
33 kg.

15-20TL M
45 kg.

30TL M
55 kg.

BATTERY INPUT (DC)	10TL M	15TL M	20TL M	30TL M
Voltage range ⁽¹⁾	120 - 600 V	120 - 800 V	120 - 800 V	120 - 800 V
Nominal battery voltage	250 - 600 V	285 - 800 V	380 - 800 V	230 - 800 V
Maximum charge / discharge current	50 / 50 A	60 / 60 A		2*75 / 2*75 A
Maximum charge / discharge power	15,000 / 11,300 W	30,000 / 15,000 W	30,000 / 20,000 W	45,000 / 30,000 W
Maximum voltage	600 V	800 V	800 V	800 V
Type of battery ⁽²⁾	Ion-lithium (LG, BYD, Pylontech...)			
Communication with ion-lithium batteries	CAN Bus 2.0			
Battery connection way	Dedicated DC connector			

PV INPUT (DC)

PV array maximum power	15,000 W	30,000 W	30,000 W	45,000 W
MPPT Voltage range	160 - 950 V			
Maximum input voltage ⁽³⁾	1,000 V			
Maximum current per MPPT (input 1 / input 2 / input 3)	20 / 30 A	32 / 32 A	32 / 32 A	32 / 32 / 32 A
Maximum short circuit current (input 1 / input 2 / input 3)	30 / 40 A	40 / 40 A	40 / 40 A	40 / 40 / 40 A
Number of MPP trackers	2	2	2	3
Number of inputs per MPP	1 / 2	2 / 2	2 / 2	2 / 2 / 2
Full power MPP voltage	370-800 V	260-800 V	350-800 V	350-800 V
PV connection way	MC4 / H4			

GRID / GENSET (AC)

Rated voltage	380 / 400 / 415 V, 3N~+PE			
Voltage range	260 - 520 V (Adjustable)			
Nominal Frequency	50 / 60 Hz			
Network type	TT / TN-C / TN-C-S / TN-S			
Rated power	10 kW	15 kW	20 kW	30 kW
Max. Temperature for rated power	45°C			
% of rate power @ 50°C	80 %			
Nominal current	3*15.2A	3*22.8A	3*30.4A	3*45.6A
Power Factor	>0.99 Rated power (Adjustable 0.8 LG-0.8 LD)			
Adjustable Power Factor	YES			
THD	<5%	<3%	<3%	<3%
AC connector type	OT Terminal			

CRITICAL LOAD (BACKUP AC)

Rated voltage	380 / 400 / 415 V, 3N~+PE			
Nominal Frequency	50 / 60 Hz			
Rated power	10 kW	15 kW	20 kW	30 kW
Nominal current	3*15.2A	3*22.8A	3*30.4A	3*45.6A
THDV	<3% (R Load), 8% (RCD Load)			
AC connector type	OT Terminal			
Overload capacity	$\geq 1.1 \cdot P_n \sim < 1.2 \cdot P_n$ (5min) $\geq 1.2 \cdot P_n \sim < 1.5 \cdot P_n$ (10s) $\geq 1.5 \cdot P_n$ (200ms)			

FEATURES

Back-up function response time	12 ms			
Max. Efficiency (PV to grid)	$\geq 97.5 \%$	$\geq 97.5 \%$	$\geq 97.5 \%$	$\geq 97.6 \%$
European Efficiency (PV to grid)	$\geq 97.1 \%$	$\geq 97.1 \%$	$\geq 97.1 \%$	$\geq 97.1 \%$
Max. Charge Efficiency (PV to battery)	$\geq 98.0 \%$	$\geq 98.0 \%$	$\geq 98.0 \%$	$\geq 98.5 \%$
Max. Discharge Efficiency (Battery to grid)	$\geq 97.1 \%$	$\geq 97.1 \%$	$\geq 97.1 \%$	$\geq 97.4 \%$
Max. Charge Efficiency (Grid to battery)	$\geq 96.7 \%$	$\geq 96.7 \%$	$\geq 96.7 \%$	$\geq 96.7 \%$

Notes

⁽¹⁾ The maximum power supplied by the battery shall be the battery voltage multiplied by the maximum discharge current.

⁽²⁾ Consult the Ingeteam website for a list of compatible batteries.

⁽³⁾ Never exceed. Consider the voltage increase of the panels 'Voc' at low temperatures.

GENERAL INFORMATION

Anti-corrosion	C4H protection class			
Refrigeration system	Natural ventilation	Natural ventilation	Natural ventilation	Forced ventilation
Stand-by consumption	<20 W			
Consumption at night	<10 W			
Ambient temperature	-25 °C to 60 °C			
Relative humidity (non condensing)	0 - 100%			
Protection class	IP65	IP66	IP66	IP66
Marking	CE			
Acoustic emissions	<30 dB	<35 dB	<35 dB	<60 dB
Max. altitude - Max. altitude without derating	4,000 m - 2,000 m			
EMC and security standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3, EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 62109-2, IEC62103, EN 50178, FCC Part 15, AS3100			
Grid connection standards	IEC 61727; IEC 62116; EN 50549-1; UNE 217002; UNE 217001; NTS SEPE 2.1 typeA; CEI 0-21 V1 November 2022 (Including Allegato A+ Allegato B+, Allegato BBis); VDE-AR-N 4105:2018.			

Notes

- ⁽¹⁾ The maximum power supplied by the battery shall be the battery voltage multiplied by the maximum discharge current.
⁽²⁾ Consult the Ingeteam website for a list of compatible batteries.
⁽³⁾ Never exceed. Consider the voltage increase of the panels 'Voc' at low temperatures.

EUROPE

Ingeteam Power Technology, S.A.
Avda. Ciudad de la Innovación, 13
31621 Sarriguren (Navarra) - Spain
Tel.: +34 948 288 000
Fax: +34 948 288 001
e-mail: solar.energy@ingeteam.com
bess.energy@ingeteam.com

Ingeteam S.A.
Parque Tecnológico de Bizkaia
Edificio 106
48170, Zamudio (Bizkaia) – Spain
Tel.: +34 944 039 710

Ingeteam S.r.l.
Via Emilia Ponente, 232
48014 Castel Bolognese (RA) - Italy
Tel.: +39 0546 651 490
Fax: +39 054 665 5391
e-mail: italia.energy@ingeteam.com

Ingeteam SAS
140 Rue Carmin - Le Naurouze B
31670 Labège - France
Tel.: +33 (0)5 61 25 00 00
Fax: +33 (0)5 61 25 00 11
e-mail: france@ingeteam.com

Ingeteam, a.s.
Technologická 371/1
70800 Ostrava - Pustkovec
Czech Republic
Tel.: +420 597 476 820
Fax: +420 59 732 6899
e-mail: czech@ingeteam.com

Ingeteam GmbH
Grand Bateau – Zollhof 6
D-40221 – Düsseldorf, Germany
Tel.: +49 (0) 211 78177950
e-mail: deutschland@ingeteam.com

Ingeteam Poland Spzoo
Ul. Koszykowa 60/62 m 39
00-673, Warsaw, Poland
Tel.: (+48) 22 821 99 30
e-mail: polska@ingeteam.com

Ingeteam LTD.
1st Floor, Midas House, 62 Goldsworth Road,
Woking, Surrey GU21 6LQ - United Kingdom
Tel.: +44 (0) 141 488 5290

NORTH AMERICA

Ingeteam Inc.
3550 W. Canal St.
Milwaukee, WI 53208 - USA
Tel.: +1 (414) 934 4100 / +1 (855) 821 7190
Fax: +1 (414) 342 0736
e-mail: usa@ingeteam.com

Ingeteam Power Technology S de RL de CV
Av. Ejercito Nacional Mexicano 351, Chapultepec
Morales, Granada, Manuel Hidalgo
CP: 11520
Ciudad de México, México
Tel.: (+52) 55 3000 1750
e-mail: proveedores.iptm@ingeteam.com

SOUTH AMERICA

Ingeteam Ltda.
Rua Estácio de Sá, 560
Santa Genebra
Campinas - SP
CEP: 13080-010; São Paulo - Brazil
Tel.: (+55) 19 30 37 37 73
e-mail: brazil@ingeteam.com

Ingeteam Chile SpA
Balmoral n.º 309, Piso 10º, Oficina 1008,
7561282 Las Condes
Santiago, Chile
Tel.: (+56) 229 253 825
e-mail: chile@ingeteam.com

ASIA

Ingeteam Power Technology Shanghai, Co. Ltd.
Room 2606-F, No.360 South Pudong Road
China (Shanghai) pilot free trade zone
C.P 200120
Tel.: +86 139 1622 4886
e-mail: liu.yimin@ingeteam.com

Ingeteam India Pvt. Ltd.
Survey No. 111/1-111/3 & 111/5-111/7,
Village No.155, Mambakkam Village,
Chennai - Bangalore Main Road,
Sriperumbudur Taluk,
Kancheepuram District - 602106,
Tamilnadu, India

Ingeteam Power Technology S.A. UAE Branch
Al Bateen tower c6 Bainunah 1st floor
Street 34
Abu Dhabi - UAE
Tel.: +971 2 207 6666

Ingeteam Power Technology S.A.
Thailand representative office
100/67 Vongvanij B Building, 22nd floor,
Rama IX Road., HuayKwang,
10320 Bangkok
Te.: +66 22461798
e-mail: Thailand.pga@ingeteam.com

Ingeteam Vietnam CO., LTD
Spaces Building, 28A Tran Hung Dao Street,
Phan Chu Trinh Ward Hoan Kiem District,
Hanoi City, Vietnam

AUSTRALIA

Ingeteam Australia Pty Ltd.
Iaccelerate Centre, Building 239
Innovation Campus, Squires Way
North Wollongong, NSW 2500 - Australia
Tel.: +61 429 111 190
e-mail: australia@ingeteam.com

Ingeteam

www.ingeteam.com